

**GO – THE POWERFUL
HELPER THAT IS GOOD
FOR YOUR BACK AND
YOUR HEALTH.**



EUROPEAN CONFORMITY



MADE IN DENMARK



A universal lifter that covers a range of uses – such as in supermarkets, workshops, warehouses and offices, as well as pharmacies and libraries. Wherever heavy objects such as goods, work material, printing paper, files or even such items as beverage crates have to be transported from A to B, lifted onto shelves or removed from shelves – the mobile lifter **GO** is the right choice. It enables effortless loads up to 70 kg up to a height of 1.50 m. Thanks to a charging unit supplied, **GO** can easily be recharged for ongoing use at a standard power socket. What is more, it is supplied in a box for self-assembly at an unbeatably low price – in the robust quality that Hovmand is well-known for.



MAXIMUM LOAD CAPACITY



OUTSTANDING ERGONOMICS



MOBILE AND AGILE



GOOD MANUFACTURING PRACTICE



TECRAM

Route d'Yverdon 34 · CH-1373 Chavornay · +41 24 441 42 40 · info@tecram.ch · www.tecram.ch

www.hovmand.com

HOVMAND
LIFTING & MOVING TECHNOLOGY

VERY SIMPLE TO USE

The moving wheels means the mobile lifter is especially easy to turn, so it can be manoeuvred within a very confined space. Parking brakes on the rear wheels ensure secure loading and unloading.




The chassis houses the charging socket and the on/off switch. It is very simple to charge the battery and switch the lifter on and off.



Charging socket and on/off switch

On the wooden platform, material can be shifted conveniently to the required working height without physical strain.



There are adjustment screws on the handle that allow it to be adjusted to the user's height within a defined range. The load is raised and lowered by means of a control lever directly on the handle. The automatic soft-start function ensures smooth operation, avoiding any jerky movements.



TECHNICAL SPECIFICATIONS:

GO mobile lifter

Load capacity: 70 kg

Lifting height:
min. 120 mm / max. 1,505 mm

Height of device: 1,700 mm

Lifting base: Wooden platform,
434 x 418 mm

Chassis:
450 x 379 mm (L x B, inside)

Lifting speed: 125 mm/sec

Battery voltage V/Ah: 24/7.2

Weight without packaging:
26 kg

Weight with packaging:
29.7 kg

